



NEW!

PORTABLE MONITOR

PARTNER 2

Portable ground monitor EN15-767 certified

- Flow up to 3000 l/min
- High elevation up to 85° (from 25°)
- **Optional safety valve** in case of movement which reduces but doesn't stop the flow to keep enough flow for a good protection to the firefighter and reduces water hammer
- **Optional self-oscillating system** with adjustable angle between 10 and 40°
- Horizontal operation -20 to +20°
- Compact size in folded position
- Equipped with a **protected pressure gauge**
- 5 flexible **stainless-steel legs**
- Body in **hard coat anodized aluminum**
- **Full time swivel inlet** 2.5" BSP F or 4" BSP M



Protected pressure
gauge and optional
safety valve

As part of our policy of constant research to improve our products, we reserve the right to modify our products' characteristics at any time without notice

Characteristics

Model (without nozzle)	Weight	Dimensions Length x width x height	Item numbers	Inlet
Partner 2* Without safety valve	9.9 kg	Folded: 51 x 24 x 32	CPA-019-OP	2.5" BSP F
Partner 2 ** with Safety valve	10.2 kg	Unfolded: 64 x 65 x 32	CPA-022-OP	2.5" BSP F
			CPA-022-8P	4" BSP M
Oscillating Partner 2 *** with Safety valves	13.8 kg	Folded: 76 x 36 x 36	CPA-122-OP	2.5" BSP F
		Unfolded: 71 x 65 x 36	CPA-122-8P	4" BSP M



* Without safety valve



** with Safety valve



*** Oscillating with Safety valves

Options

Tips:

- **OneFlow:** fixed flow monitor nozzle
Ref: CDA-023-OI: 2000 l/min @ 6 bar
- **FlowMatic:** automatic monitor nozzle
Ref: CDA-020-OI: 2000 l/min @ 6 bar
Ref: CDA-021-OI: 3000 l/min @ 6 bar

Accessories:

- **storage bracket** in stainless steel
Weight: 3.1kg / 6.9 lbs
Dim: 5 x 25 x 49 cm / 2" x 9.9" x 19.3"
Ref: CDA-200-II
- **Inlet couplings** on request:
BS336,
Storz,
DSP,
Barcelona...



Reduced cost of ownership:

Very light maintenance requirement due to the nozzle design and materials used.



ZF.02.292.EN.2