

ICARE

FIREFIGHTING BOOTS

EN 15090 : 2012



F2A
SRC HI3 CI



- Undetectable when passing through security check
- High upper for a better protection
- Metal free



Boche Lacing System



Rubber pump cap

UPPER 2,2 ± 0,2mm black grain leather,
Fire resistant and waterproof,
Combined with a breathable fabrics highly resistant
to abrasion.

INNER LINING Sympatex high2Out®,
Imper-breathing membrane,
100% waterproof and breathable,
The moisture is transported away efficiently.

TOECAP Light XXL Fiberglass,
Metal free and athermic, providing more comfort
in use.

RUBBER PUMP CAP Fire resistant rubber protection 1,7mm,
Stitched and cemented,
High abrasion resistance.

SHOELACE Boche lacing system:
Easy use, safe, light,
High resistance to shocks and fire.

INSOLE Removable comfort insole,
High density foam for maximum comfort and shock
absorption,
Anatomic shape,
Antistatic.

WEIGHT 1.95 kg size 42

SIZE 35 to 50 (Europe)
3-14 (UK)


SOLING TECHNOLOGY Cemented assembly
Nitrile rubber outsole,
Extremely slip resistant (SRC),
High abrasion resistance,
Antistatic,
High heat resistance (>300°) (HRO),
Heat (HI3) and cold (CI) insulation,
Possibility to have the sole redone as the original one,



WEIGHT : 1.9kg



METAL FREE



LEATHER
THICKNESS



SYMPATEX
LINING



SHOCKS
ABSORPTION



FIBERGLASS
TOECAP



CEMENTED
ASSEMBLY



PROTECTIVE
TEXTILE MIDSOLE

Protective textile midsole:
Pro Tector Z,
High flexibility,
Thermal insulation,
No metal part.